

### Product Description

Hard and durable polyurethane / crosslinking acrylic enamel for interior use.  
Excelent for woodwork and primed metal, where an extra tough surface is needed.

### Directions for use

The substrate must be sound/stable, dry, clean, and free from all substances that may prevent good adhesion.  
New wood should be primed with suitable water-borne primer. If necessary, use a suitable undercoat, followed by 2 coats of PU Enamel  
Previously painted surfaces to be prepared and suitable for applying the top coat before applying the top coat. Iron and metal should be primed with suitable primer before applying the top coat.

### Cleaning instructions

Cleaning with clean water, preferably added a little detergent, immediately after use.

### Sprayguide

Spraying	Nozzle	Air pressure	Ass. Air	Filter
Airless with Finefinish	10-14 (graco)			100 mesh

### Technical data

<b>Binder:</b>	Polyurethane and crosslinking acrylic
<b>Type:</b>	
<b>Gloss:</b>	Approx. 30, semigloss
<b>Vol. dry:</b>	App. 35%
<b>Colours:</b>	White and Clear. Can be tinted
<b>Drying:</b>	2-4 hours, recoatable after approx. 12 hours at +20 °C og 65% RF
<b>Application:</b>	+10 °C to + 25° C. RH: 40-80%
<b>Thinning:</b>	Water
<b>Coverage:</b>	8-10 m <sup>2</sup> /ltr
<b>Tools:</b>	Brush, Roller or Spraying
<b>Mal-Code:</b>	00-1 (1993)

